

## Kerotite Curb Stop-Nylon Valves

### Features:

- Tested to ANSI B16.40
- Unobstructed circular opening
- Balanced plug design
- 12 degree shut off assurance
- 90 degree or 360 degree operation
- Can use curb or street key
- Fits existing curb boxes
- User friendly mechanical connections
- Rated for 100 PSI gas service



### Valve Make-up:

1. Zytel plug with integral Xenoy actuator
2. Buna "N" weaterseal against ground water
3. Zytel nylon valve body
4. Polyurethane valve seat
5. Low temperature Buna "N" plug seal
6. Zytel nylon nut
7. Buna "N" gasket
8. Stainless steel washer
9. Celcon grip ring
10. Stainless steel retaining ring
11. Polyethylene dust cover
12. Plated steel stiffener



## Valve Selection Code Number

Size (inches)	Part #	Service Rating	End to End (in)	Height (inches)	Port Dia. (inches)	Weight
1/2 CTS	CS-0625	100 PSI	6-5/8	4-1/2	0.50	1 lb
1/2 CTS x 3/4 IPS	CS-0575	100 PSI	6-5/8	4-1/2	0.50	1 lb
3/4 IPS	CS-1050	100 PSI	6-5/8	4-1/2	0.75	1 lb
3/4 CTS	CS-0875	100 PSI	6-5/8	4-1/2	0.75	1 lb
1 CTS	CS-1125	100 PSI	6-5/8	4-1/2	0.79	1 lb
1 IPS	CS-1315	100 PSI	10	6	1.00	3 lb
1-1/4 CTS	CS-1375	100 PSI	10	6	1.00	3 lb
1-1/4 IPS	CS-1660	100 PSI	10	6	1.00	3 lb

\* Service Rating limiting factor is SDR rating of pipe used. Valves are quarter turn - For 360 degree operation, add minus 360 degree part number.