Series PB410

Heavy Duty Pressure Balancing Protection

- Proven reliable diaphragm-and-poppet cartridge design won't stick, seize or corrode due to harsh water conditions
- Rugged commercial grade four-port bronze casting with brass bonnet and metal-to-metal, temperature limit stop
- Integral check stops for easy access and maintenance
- · Compact design fits into as little as 2" wall depth
- Back-to-back installation without costly cross-over piping
- ASSE 1016 listed and CSA B125 certified
- Won't stick or seize due to harsh water conditions
- Self-contained cartridge installs in minutes to simplify maintenance

Serving hotel, healthcare, education, commercial and residential markets since 1891.











COMPLIANCE




PERFORMANCE DODUTETTODOLLETTOTOTODO

HydroGuard®

Series PB410

Powers offers you complete shower systems...

- Ideal for demanding applications like health clubs, schools, and hotels
- Back-to-back installation without costly crossover piping by simply rotating the stem 180° and re-labeling the ports
- Optional HT115 valve easily threads into showerhead assembly for added protection against scalding
- Hundreds of Configurations







Optional HT115 ScaldStop™ shuts down water if temperature reaches 115° or greater.





PB417M1U0000 Tub and Shower Assembly Shown

System components combine beauty and functionality...



Deluxe chrome-plated brass faceplate and handle provide lasting performance and an attractive appearance.



Showerheads are available in four models: deluxe chrome-plated brass, standard chrome-plated brass, adjustable massage, and economizer chrome-plated ABS. Arm and flange options include standard and deluxe chrome plated brass.



141 409 Shown

Tub spouts are available with and without diverters in 1/2" and 3/4" inlets. All spouts are chrome-plated.



Diverters are available concealed or exposed. Vacuum breakers are available as elevated with chrome plating, or as in-line.











ISO 9001-2008 CERTIFIED

A Watts Water Technologies Company